

REFLEX A MOPCLOTH

	Make a difference with REFLEX: Outstanding Performance & Versatility: Deep Cleaning. Multifunctional and Ergonomical. Up to 50 sqm more per mopcloth. Outstande & Eco-friendly: Less water and chemicals. Residue Free Cleaning.				
	Product	roves cleaning economy: s time and space and cuts total costs. Colour code: Dimensions:			
	code:				
	18-0057	Grey 4 colour tags	54 x 16 cm	REFLEX A MOPCLOTH 100% Micro, Multiple use, 175 grs/pcs	
Package: 5 pcs pp bag 20 pcs x 5-pack per transport b			ick per transport box		
Application areas:		The REFLEX 2-in-1 cleaning system is designed for all types of smooth and sealed hard top floorings. Main application areas:			
		Healthc sector	are [Public Areas & General Buildings & Food Industry & HoReCa	
How to use the system:		REFLEX A MOPCLOTH is double-sided and is used in conjunction with REFLEX POWER SQUEEGEE 50 cm and REFLEX EXTENDABLE HANDLE 100/180 cm.			
		CHARGING: REFLEX A MOPCLOTHS can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.			
		CHARGING A MOPCLOTHS ON THE TROLLEY: 1. Put A MOPCLOTHS in a container, e.g. 6 Ltr. rectangle bucket or box with lid. 2. Pour the desired fluid equally over the cloths inside the container. 3. Leave for a while with closed lid. Ready to clean!			
		ABOUT DOSING: Avoid overdosing regardless of the charging liquid. Some chemicals may cause damage to user, material and/or environment. Depending on floor circumstances, charge the A MOPCLOTHS with 100-200 ml per cloth.			
RESIDUE FREE CLEANING		Rekola supports Residue Free Cleaning. Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health. REFLEX A MOPCLOTHS are designed to reduce and remove residue that resist traditional cleaning methods. For more information please contact Rekola.			

RGKOLS

Maintenance				
Laundry:	Rinse twice with cold water to ensure all cleaning chemicals are removed.			
والم	Main program for synthetic fibres at 60°C or less is preferred.			
	Rinse twice at 40°C to ensure all laundry agents are removed.			
	Adjust temperatures and water volumes accordingly.			
	Machine drum can be filled with A MOPCLOTHS up to 80% load			
	(according Weber & Leucht laundry test DIN EN ISO 6330).			
	In case of drying use tumble drying at 40°C.			
	Do not use bleach or softener.			
	Low water level during processing or overloading the washing machine (max 80%			
	of door window) may cause irreversible damage to cloths.			
Disinfection:	Non–bleach disinfectant* laundry agent and autoclaving may be used if required. *e.g. peroxide based; this may affect colours			
Durability:	500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough surfaces like			
	safety flooring may reduce the cloth's lifetime expectations.			
Components				
Body:	100% PE Microfibre.			
Backside:	PES Mesh.			
Borders:	Overlock 100% PES. Sliding strip TPU and PES Mesh.			
Characteristics				
Shrinkage:	Tested < 6% at recommended washing instructions. This can cause slight			
	deformation, which does not affect the functionality.			
Colour fastness:	4-5 standard request ≥ 3-4			
Non-touch:	In conjunction with REFLEX POWER SQUEEGEE, dirty cloths are not touched when demounting.			
Patent:	FI201000028 Floor Maintenance Device and Cloth			
Disposing:	REFLEX A MOPCLOTHS are purely synthetic: they may be used for recycling			
	programs, or because of their high energy value and zero emissions other than CO ₂ and water, can be safely disposed by controlled energy-supply programs.			
Guarantee	and water, can be safety disposed by controlled energy-supply programs.			
	d laundry according to producer's guidelines at 60°C, under general hygiene cleaning			
	nd at a maintained non-safety sealed floor.			
Extended usage can be achieved if optimal laundry and cleaning conditions are considered				
For instructions a	nd details, contact your local distributor.			

REKOLA OY, Rutintie 3 , FI-04600 Mäntsälä FINLAND tel. +358 19 687 35 16 fax. +358 19 687 35 18 http://www.rekola.com