

REFLEX G MOPCLOTH

Make a difference with REFLEX:



Outstanding Performance & Versatility:

Deep Cleaning. Multifunctional and Ergonomical. Up to 50 sqm more per mopcloth.



Climate & Eco-friendly:

Less water and chemicals. Residue Free Cleaning.



Improves cleaning economy:

Saves time and space and cuts total costs.

| Product code: | Colour code: | Dimensions: | |
|---------------|-----------------|--------------|-----------------------------------|
| 18-4050 | blue | 54 x 22,5 cm | REFLEX G MOPCLOTH 50% UMF, 50% PE |
| | | | Multiple use, 88 grs/pcs |
| 18-4054 | red | 54 x 22,5 cm | REFLEX G MOPCLOTH 50% UMF, 50% PE |
| | | | Multiple use, 88 grs/pcs |
| Package: | 5 pcs pp | bag 🏟 32 pc | s x 5-pack per transport box |

Application areas:

The REFLEX 2-in-1 cleaning system is designed for all types of smooth and sealed hard top floorings. Main application areas, in case of less conditioned floors:



Public Areas & General Buildings



Food Industry & HoReCa

How to use the system: REFLEX G MOPCLOTH is double-sided and is used in conjunction with REFLEX POWER SOUEEGEE 50 cm and REFLEX EXTENDABLE HANDLE 100/180 cm.



CHARGING:

REFLEX G MOPCLOTHS can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.

CHARGING G MOPCLOTHS ON THE TROLLEY:

- 1. Put G MOPCLOTHS in a container, e.g. 6 Ltr. rectangle bucket or box with lid.
- 2. Pour the desired fluid equally over the cloths inside the container.
- 3. Leave for a while with closed lid. Ready to clean!

ABOUT DOSING:

Avoid overdosing regardless of the charging liquid.

Some chemicals may cause damage to user, material and/or environment. Depending on floor circumstances, charge the G MOPCLOTHS with 60-120 ml per cloth.

Eco-labelled:



0027

Rekola supports Residue Free Cleaning.

Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health. REFLEX G MOPCLOTHS are designed to reduce and remove residue that resist traditional cleaning methods. For more information please contact Rekola.



| 0.4 | | | | |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| Maintenance | Diversity of the cold control to a control of the cold control of | | | |
| Laundry: | Rinse twice with cold water to ensure all cleaning chemicals are removed. | | | |
| | Main program for synthetic fibres at 60°C or less is preferred. | | | |
| | Rinse twice at 40°C to ensure all laundry agents are removed. | | | |
| | Adjust temperatures and water volumes accordingly. | | | |
| | Machine drum can be filled with G MOPCLOTHS up to 80% load | | | |
| | (according to Weber & Leucht laundry test DIN EN ISO 6330). | | | |
| | In case of drying use tumble drying at 40°C. | | | |
| | Do not use bleach or softener. | | | |
| | Low water level during processing or overloading the washing machine (max 80% of door window) may cause irreversible damage to cloths. | | | |
| Disinfection: | | | | |
| Disinfection: | Non-bleach disinfectant* laundry agent and autoclaving may be used if require | | | |
| Durability: | *e.g. peroxide based; this may affect colours 500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough surfaces like | | | |
| Bull districtly. | safety flooring may reduce the cloth's lifetime expectations. | | | |
| | , 6 1, 1111 1 1 1111 1 1 1 1 1 1 1 1 1 1 | | | |
| | | | | |
| Components | | | | |
| Body: | 50% split Ultra Microfibre / 50% PES ; 90% PES , 10% PA . UMF F= 0,154 Dtex. | | | |
| Borders: | Overlock 100% PES. Sliding strip TPU and PES Mesh. | | | |
| Washing label: | PES colour fast. | | | |
| Characteristics | | | | |
| Shrinkage: | SGS tested < 6% at recommended washing instructions. This can cause slight | | | |
| | deformation, which does not affect the functionality. | | | |
| Colour fastness: | 4-5 standard request ≥ 3-4 | | | |
| Charging: | 3,9 DAC value standard request minimum 2,5 | | | |
| Abrasion: | 10,5 gloss differential standard request < 20 | | | |
| Weber & Leucht S301/1.3 dirt removal: | Ceramic tile SF 11 Dust A23 Damp 97% standard request ≥ 70 | | | |
| | PVC flooring PL-03 Dust A23 Damp 90% standard request ≥ 70 | | | |
| | Ceramic tile SF 11 Muddy dirt A05 Damp 100% standard request ≥ 70 | | | |
| | PVC flooring PL-03 Muddy dirt A05 Damp 100% standard request ≥ 70 | | | |
| Non-touch: | In conjunction with REFLEX POWER SQUEEGEE, dirty cloths are not touched when demounting. | | | |
| Patent: | FI2010000028 Floor Maintenance Device and Cloth | | | |
| Disposing: | REFLEX G MOPCLOTHS are purely synthetic: they may be used for recycling | | | |
| Disposing. | programs, or because of their high energy value and zero emissions other than CO ₂ | | | |
| | and water, can be safely disposed by controlled energy-supply programs. | | | |
| Guarantee | | | | |

Guarantee

500 times use and laundry according to producer's guidelines at 60°C, under general hygiene cleaning circumstances, and at a maintained non-safety sealed floor.

Extended usage can be achieved if optimal laundry and cleaning conditions are considered.

For instructions and details, contact your local distributor.