

### **REFLEX H MOPCLOTH**



Outstanding Performance & Versatility:

Deep Cleaning. Multifunctional and Ergonomical. Up to 50 sqm more per mopcloth.



Climate & Eco-friendly:

Less water and chemicals. Residue Free Cleaning.



Improves cleaning economy:

Saves time and space and cuts total costs.

Product code:	Colour code:	Dimensions:	
18-2050	blue	54 x 22,5 cm	REFLEX H MOPCLOTH 100% UMF, Multiple use, 88 grs/pcs
18-2054	red	54 x 22,5 cm	REFLEX H MOPCLOTH 100% UMF, Multiple use, 88 grs/pcs
18-2055	green	54 x 22,5 cm	REFLEX H MOPCLOTH 100% UMF, Multiple use, 88 grs/pcs
18-2056	yellow	54 x 22,5 cm	REFLEX H MOPCLOTH 100% UMF, Multiple use, 88 grs/pcs
Package:	5 pcs pp	bag 🕸 32 pc	s x 5-pack per transport box

**Application** areas:

The REFLEX 2-in-1 cleaning system is designed for all types of smooth and sealed hard top floorings. Main application areas:



Healthcare sector



**Public Areas** & General Buildings



Food Industry & HoReCa

How to use the system: REFLEX H MOPCLOTH is double-sided and is used in conjunction with REFLEX POWER SOUEEGEE 50 cm and REFLEX EXTENDABLE HANDLE 100/180 cm.



### **CHARGING:**

REFLEX H MOPCLOTHS can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.

#### CHARGING H MOPCLOTHS ON THE TROLLEY:

- 1. Put H MOPCLOTHS in a container, e.g. 6 Ltr. rectangle bucket or box with lid.
- 2. Pour the desired fluid equally over the cloths inside the container.
- 3. Leave for a while with closed lid. Ready to clean!

#### ABOUT DOSING:

Avoid overdosing regardless of the charging liquid.

Some chemicals may cause damage to user, material and/or environment. Depending on floor circumstances, charge the H MOPCLOTHS with 60-120 ml per cloth.

## Eco-labelled:



3083 0027



## Rekola supports Residue Free Cleaning.

Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health. REFLEX H MOPCLOTHS are designed to reduce and remove residue that resist traditional cleaning methods. For more information please contact Rekola.



Maintenance					
Laundry:	Rinse twice with cold water to ensure all cleaning chemicals are removed.				
	Main program for synthetic fibres at 60°C or less is preferred.				
	Rinse twice at 40°C to ensure all laundry agents are removed.				
	Adjust temperatures and water volumes accordingly.				
	Machine drum can be filled with H MOPCLOTHS up to 80% load				
	(according to Weber & Leucht laundry test DIN EN ISO 6330).				
	In case of drying use tumble drying at 40°C.				
	Do not use bleach or softener.				
	Low water level during processing or overloading the washing machine (max 80%				
	of door window) may cause irreversible damage to cloths.				
Disinfo ation	<u> </u>				
Disinfection:	Non-bleach disinfectant* laundry agent and autoclaving may be used if required.  *e.g. peroxide based; this may affect colours				
Durability:	500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough surfaces like				
	safety flooring may reduce the cloth's lifetime expectations.				
Components					
Body:	100% split <b>Ultra Microfibre</b> ; 80% <b>PES</b> , 20% <b>PA</b> . F= 0,154 Dtex.				
Borders:	Overlock 100% PES. Sliding strip TPU and PES Mesh.				
Washing label:	PES colour fast.				
Characteristics					
Shrinkage:	SGS tested < 6% at recommended washing instructions. This can cause slight deformation, which does not affect the functionality.				
Colour fastness:	4-5	standard request <u>&gt;</u> 3-4			
Charging:	3,7 DAC value standard request minimum 2,5				
Abrasion:	6,8 gloss differential standard request < 20				
Weber & Leucht	Ceramic tile SF 11 Dust A23	Damp 100% <i>standard request ≥ 70</i>			
S301/1.3 dirt	PVC flooring PL-03 Dust A23	Damp 95% <i>standard request <u>&gt;</u> 70</i>			
removal:	Ceramic tile SF 11 Muddy dirt	A05 Damp 100% <i>standard request <u>&gt;</u> 70</i>			
	PVC flooring PL-03 Muddy dirt	A05 Damp 100% <i>standard request <u>&gt;</u> 70</i>			
Bacteria	E-coli 99,9% log > 5,34				
reduction:	S. Aureus 99,85% log 2,82				
Non-touch:	In conjunction with REFLEX POWER SQUEEGEE, dirty cloths are not touched when				
	demounting.				
Patent:	FI2010000028 Floor Maintenance Device and Cloth				
Disposing:	REFLEX H MOPCLOTHS are purely synthetic: they may be used for recycling				
Disposing.		· · · · · · · · · · · · · · · · · · ·			
Disposing.	programs, or because of their high	energy value and zero emissions other than CO <sub>2</sub> by controlled energy-supply programs.			

# Guarantee

500 times use and laundry according to producer's guidelines at 60°C, under general hygiene cleaning circumstances, and at a maintained non-safety sealed floor.

Extended usage can be achieved if optimal laundry and cleaning conditions are considered. For instructions and details, contact your local distributor.